

EXPLOSIONSZEICHNUNG



KBS Gastrotechnik GmbH – Schoßbergstraße 26 – 65201 Wiesbaden



T&S BRASS AND BRONZE WORKS, INC.


2 Saddleback Cove / P.O. Box 1088
Travelers Rest, SC 29690

Model No.

EU-3192-VL15

Item No.


Travelers Rest, SC: 800-476-4103 • Simi Valley, CA: 800-423-0150 • Fax: 864-834-3518 • www.tsbrass.com



ITEM NO.	SALES NO.	DESCRIPTION
1	B-0199-M21-VL15	Cache Concealed Laminar Device, 1.5 GPM
2	020330-45	Solenoid Valve, M22 x 2 Male Thd
3	019087-45	6VDC Lithium Battery, CR-P2
4	020417-45	Aux. Power Connector Cable
5	5EF-0011C	AC Adapter - EU Type Plug
6	020270-45	Lever Asm & Body Screw Kit w/ L-Key
7	020967-45	Supply Hose, 9/16-24 Female x G 1/2" (EU)
8	020883-40	1/2" NPSM Check Valve Adapter Body
9	020498-25	Hex Bushing, G 3/8" Female x 1/2 NPSM Male w/ Sealing Washer
10	020426-40	Body Plug, Pre-Set Temperature



A maximum of (8) ChekPoint faucets can be powered by EC-HARDWIRE ChekPoint Hardwire AC Transformer when connected using EC-ADEWIRE cables. (Both sold separately)



Optional Plug When
Pre-setting Temperature
(Installs from Inside of Body)



020760-45
Sensor Range
Set-Up Magnet



020674-45
VR Aerator Key



018543-45
Torx T-20
VR L-Key

Flow Control Switches are Located Behind the Sensor. Switches are set to DEFAULT position:

- Auto Time Out = 15 seconds
- Shut Off Delay = 1 second
- Auto Flush = OFF
- Metering Mode = OFF

Available Water Flow Control Selections:

- Auto Time Out: 15 sec, 30 sec, 45 sec, 60 sec, 3 min, 20 min
- Shut Off Delay: 1 sec, 10 sec, 15 sec, 30 sec
- Auto Flush (30 Seconds After Every 12 Inactive Hours): ON or OFF
- Metering Mode = ON or OFF

Product Specifications:

Chrome Plated Brass Above Deck Electronics Faucet, Single Hole Deck Mount, Cast Spout, 1.5 GPM VR Concealed Laminar Device, Point-of-Use Temperature Control, Battery or AC Adapter Powered, EU Transformer, Stainless Steel Flexible Supply Lines & G3/8 Female Adapter Inlets

Product Compliance:

CE
DVGW
RoHS

Drawn: DMH Checked: JRM Approved: JHB Date: 04/01/25 Scale: NTS Sheet: 2 of 2