



-Rough-In Requirement:
29mm Mounting Hole

-Nominal Flow Rate: 5l/min (spout);
14 l/min (spray valve).

PRODUCT COMPLIANCE:

ROHS 2011/65/UE;
REACH 1907/2006;
DVGW Hygiene

TITLE / DESCRIZIONE SHRINK, 60cm tall, deck mount Pre Rinse Unit. Chrome plated brass single hole; mixing temperature; 105mm long G3/4" mounting shank; G3/8" female inlets with check valves; 250mm swivel nozzle (Ø20); 220mm long sanitary lever; high flow ceramic cartridge; stainless steel riser tube; 14l/min KLARCO "BEST SEMI"spray valve; black details.	DRN / DIS	CHD / VER	APPR
	A.E.		
SCALE / SCALA	DATE / DATA	SHEET / PAG	
1:9	23/12/22	1 of 2	
NUMBER / CODICE DIS.	MODEL / PRODOTTO		
	260N.R080N		

This drawing contains proprietary information which is the property of KLARCO S.R.L. without whose written permission it may not be copied, shown or handed to a third party or otherwise used

Questo disegno contiene informazioni di proprietà di KLARCO S.R.L. e senza la sua autorizzazione scritta non può essere copiato, mostrato o ceduto a terzi o in qualsiasi altro modo usato